

NEUTRAL SOFTBOARD (NEUDLSB10)

Description:




- Multilayered soft board from wood fibers
- FSC certified
- Reduces impact sound
- High walking comfort
- Compensate for minor height differences
- Compatible with floor heating
- Rigid construction - very suitable for installation under click floors
- Easy to install



Technical characteristics:

- Dimensions: panels of 790 mm x 590 mm
- Packing Unit: 1 pack = 22 panels
- Total surface area of 1pack: 10.25m²
- Thickness: 4mm

Test results:

 <p>Transmission sound The sound that travels down through the floor and can be experienced as annoying by neighbors on the level below</p>	<ul style="list-style-type: none"> ○ Result: ΔL_w (dB): 17-19 dB ○ Norm: ISO 140-8 norm. ○ Institute: CTBA
 <p>Heat resistance Suitable for underfloor heating</p>	<ul style="list-style-type: none"> ○ Result: R-value: 0.06m²K/W. ○ Norm: EN 12664 ○ Institute: In company
 <p>Compression strength (at 0,5 mm deformation)</p>	<ul style="list-style-type: none"> ○ Result: 39 kPa (3,9 ton/m²) ○ Standard: prEN16354 ○ Institute: In-company

Installation Instructions:

If installing on a mineral subfloor apply first a PE before laying the Soft board. The floor must be clean, dry and flat.

The installation direction should be perpendicular (cross wise) the direction of the flooring. Place the sheets with a half drop displacement of the sheets between the first and second row. Continue until the entire space is covered.